

Films for surface protection: Serie F[®] - FMasking

The films for sheet surface protection are being processed through an extrusion of polyolefinic resins. Neither glues nor solvents nor additional additives of any kind are used for production.

A wide range of adhesion values and mechanical characteristics make this film highly flexible to adapt to different surfaces.

Key features

- High mechanical properties
- High scratch resistance
- Applicable to PMMA CAST, PMMA XT, PC, PS, PET, PETG, PP, ABS, SAN, ETC...
- No residue on the sheets

Film quality is ensured by the considerable experience gained by Industria Termoplastica Pavese S.p.A. in the production of special packaging materials. This quality has been certifying according to ISO 9001 since 1993.





INNOVATIVE PACKAGING SOLUTIONS



Warning

Storage precautions

Keep the rolls in their original packaging in dry environment, protected from sunlight and atmosphere agents, at a temperature of 20 (+/-10) °C. Store the material in working environment at least 24 hours before using.

Recommended use (shelf life): within 6 months from production date. Exceptions to this period, when the material is correctly stored, have been successfully experimented.

Precautions for use

The information provided in this publication has to be considered true and accurate at the time of publication. They have been obtained using laboratory specimens and equipments. The publication of this information, however, does not represent a guarantee for further delivery. The customer should take care to determine the suitability of such product for the intended use.

Industria Termoplastica Pavese Spa

www.itp.it - E-mail: itp@itp.it

Tel. +39 0385 272711

